



KET-RMB-211.CN.DALI

Applications

Building management system

Protocol converter for DALI2 controller

- Suitable for building management systems
- CF.HD67843-B2-Y device management
- Compact size
- Wall or DIN rail mounting

KET-RMB-211.CN.DALI is able to manage via RS485 ModBUS the DALI2/ModBUS Slave converter CF.HD67843-B2-Y that can control up to 64 lamps/16 groups with DALI2 protocol.

Radio communication with the RTU with advanced BMS/BEMS functions makes it particularly suitable in a management automation ecosystem.

The device has a format suitable for mounting in a control cabinet on a DIN rail, its antenna connector supports antennas with 90° joint or with cable for positioning outside the control cabinet.

Maximum flexibility of power supply, direct from the mains or low voltage, both DC and AC..

Technical Features

General specifications	Protection Range: IP50 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity:
General specifications	Protection Range: IP50 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity: Dimensions: 53,5 x 110 x 61 mm (W x H x D) Mounting: DIN rail or Wall mounting with supplied supports Required DIN modules: 3 DIN modules Electric Board Type: Industrial or switchboard Material: Blend PC/ABS sel extinguishing UL94-VO
General specifications	Protection Range: IP50 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity: Dimensions: 53,5 x 110 x 61 mm (W x H x D) Mounting: DIN rail or Wall mounting with supplied supports Required DIN modules: 3 DIN modules Electric Board Type: Industrial or switchboard Material: Blend PC/ABS sel extinguishing UL94-VO Supply Voltage: 12 ÷ 24 VDC, 12 ÷ 20 VAC; 230 VAC with integrated power supply Consumption: < 1.5 W @ 12 ÷ 20 VAC / < 1.5 W @ 12 ÷ 24 VDC / < 1.5 W @ 230 VAC Connectors types: Screw terminal
General specifications	Protection Range: IP50 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity: Dimensions: 53,5 x 110 x 61 mm (W x H x D) Mounting: DIN rail or Wall mounting with supplied supports Required DIN modules: 3 DIN modules Electric Board Type: Industrial or switchboard Material: Blend PC/ABS sel extinguishing UL94-VO Supply Voltage: 12 ÷ 24 VDC, 12 ÷ 20 VAC; 230 VAC with integrated power supply Consumption: < 1.5 W @ 12 ÷ 20 VAC / < 1.5 W @ 12 ÷ 24 VDC / < 1.5 W @ 230 VAC Connectors types: Screw terminal Channels: Supported Protocols: ModBUS RTU Master for managing a single ModBUS/DALI converter CF.HD67843-B2-Y Communication Rate: Isolation: Connectors types: Screw terminal